Concrete Design Handbook – 4th Edition

CHAPTER 5: ADDITIONAL DESIGN AIDS

The additional design aids in this PDF document form part of the Concrete Design Handbook 4th Edition and are the exclusive property of the Cement Association of Canada. They must not be reproduced in any form without the written permission of the Cement Association of Canada.

Pages of this document were numbered sequentially with the Handbook chapter material to which they pertain, such that a user may print these design aids and add them to the hard cover book should they choose to do so.

This document has been prepared by the Cement Association of Canada (CAC) to aid in the design of reinforced concrete building structures. It has been the intent of the CAC to present this information in a manner which will serve as an extension to the CSA Group standard A23.3-14, Design of concrete structures, and the other documents referenced herein. While every attempt has been made to present information that is factual and in a useable format, none of the references to the CSA Group standard or the National Building Code of Canada should be construed as an endorsement of the material appearing in the Handbook by the agencies responsible for the referenced material.

This publication is intended SOLELY for the use of PROFESSIONAL PERSONNEL who are competent to evaluate the significance and limitations of the information provided herein, and who will accept total responsibility for the application of this information. The authors and the Cement Association of Canada disclaim any and all RESPONSIBILITY and LIABILITY for the application of the stated principles and for the accuracy of any of the material contained in this publication to the full extent permitted by law.

Concrete Design Handbook – 4th Edition Chapter 5: Additional Design Aids First printing August 2016




Table 5.1 Beam to Slab Ratio α (Edge Beams)

5–44 Slabs




Table 5.2 Beam to Slab Ratio α (Interior Beams)

5




 Table 5.3 Factor k, Shear-Moment Transfer, Interior Column

5–46 Slabs




Table 5.4 Factor k_1 or k_2 , Shear-Moment Transfer, Interior Column




Table 5.5 Factor k, Shear-Moment Transfer, Edge Column

5–48 Slabs




Table 5.6 Factor k_1 , Shear-Moment Transfer, Edge Column

5




 Table 5.7 Factor k_2 , Shear-Moment Transfer, Edge Column

5–50 Slabs




 Table 5.8 Factor k_1 , Shear-Moment Transfer, Corner Column

5




Table 5.9 Factor k_1 or k_2 , Shear-Moment Transfer, Corner Column

5–52 Slabs

Table 5.10 Area of Reinforcing Steel ($A_s \text{ mm}^2$) Per One Metre Strip

Bar Spacing mm	Bar Size (No.)					
	10	15	20	25	30	35
50	2000	4000	6000	10000	14000	20000
80	1250	2500	3750	6250	8750	12500
100	1000	2000	3000	5000	7000	10000
120	833	1667	2500	4167	5833	8333
150	667	1333	2000	3333	4667	6667
180	556	1111	1667	2778	3889	5556
200	500	1000	1500	2500	3500	5000
220	455	909	1364	2273	3182	4545
240	417	833	1250	2083	2917	4167
250	400	800	1200	2000	2800	4000
260	385	769	1154	1923	2692	3846
280	357	714	1071	1786	2500	3571
300	333	667	1000	1667	2333	3333
320	313	625	938	1563	2188	3125
340	294	588	882	1471	2059	2941
360	278	556	833	1389	1944	2778
380	263	526	789	1316	1842	2632
400	250	500	750	1250	1750	2500
420	238	476	714	1190	1667	2381
440	227	455	682	1136	1591	2273
460	217	435	652	1087	1522	2174